## V SERIES . LIGHTING

## COMPONENT PARTS/ACCESSORIES . INCANDESCENT FIXTURES



(L) Listed - File E27731



SP Certified - File LR11851



150 W Max. Lamp Size A-21



300 W Max. Lamp Size PS-25



Polycarbonate



500 W Max. Lamp Size PS-35

CATALOG NUMBER			
150 W A-21 LAMP 300 W PS-25 LAM		DESCRIPTION	
VCG-100	VCG-200	Clear	
VCGP-100	VCGP-200	Clear Tempered. Thermal and shock resistant ①	
VCGPT-100	_	Clear Tempered with Tuffskin® coating@	
VAMG-100	VAMG-200	Amber	
VGG-100	VGG-200	Blue Green	
VGGP-100	VGGP-200	Blue Green Tempered①	
VBG-100	VBG-200	Blue	
VBGP-100	_	Blue Tempered①	
VRG-100	VRG-200	Ruby	
VRGP-100		Ruby Tempered①	
VRSG-100	_	Green	
VPG-100	_	Purple	
75 W A-19 LAMP	150 W A-21 LAMP	Polycarbonate. Cannot be used with guard or in high ambien	
VPLCG-100	VPLCG-200	temperature locations (40°C/104°F max.) Not UL Listed.	
500 W PS	-35 LAMP		
VCG-500		Clear (for replacement)	
VCGP-500		Tempered. Thermal and shock resistant (for replacement).	

- 1) Recommended for use with VXFC fixture basis.
- TM Thomas Manufacturing.



V GUARDS		
CATALOG NUMBER	DESCRIPTION	
VAG-100	100 Series Vaportite guard	
VAG-200	200 Series Vaportite guard	



V REFLECTORS				
CATALOG NUMBER	DESCRIPTION			
VPRSD-100	100 Series Reflector	16 3/8" Dia. White polypropylene for pendant & ceiling applications.		
VPRSD-200	200 Series Reflector	Not for use with wall or stanchion models.		



**Body To Splice Box** Gasket 100 or 200 Series **VTG Standard** VTG-S Silicone (pictured)



Lamp Socket Gasket VTRG

V SERIES GASKETS							
CATALOG NUMBER			DESCRIPTION				
100 SERIES	200 SERIES	TYPE	DESCRIPTION				
VTG		VFC	Fixture body to splice box				
VTG-S		VXFC	Silicone, Fixture body to splice box				
v	TRG	VFC, VXFC	Porcelain lamp socket gasket				
-	VTGG	VFC	Globe gasket				
VTGG1-S	VTGG2-S	VFXC	Silicone, globe gasket				



Globe Gasket 100 Series Standard - none required 200 Series Standard - VTGG (pictured) 100 Series Silicone - VTGG1-S 200 Series Silicone - VTGG2-S



V LAMP SOCKET	
CATALOG NUMBER	DESCRIPTION
VRME	For fixture types 100 and 200