

Intrinsically Safe Permissible Multi-Function Headlamps

XPP-5458G

190 Lumens
Dual-Light™

130 Lumens
Spotlight

100/25 Lumens
Floodlight

21 Lumens
Green Floodlight



These non-rechargeable multi-function headlamps are cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible. The headlamps each feature a multi-position tilt head design, a rear-mounted battery compartment and include both an elastic head strap with a non-slip lining and a heavy-duty rubber strap for use with hard hats. The top mounted dual switches provides spotlight, full-power white floodlight, half-power white floodlight and either red (5456) or green (5458) floodlight operation. Power comes from 3 AA premium batteries (included).

**INTRINSICALLY SAFE
PERMISSIBLE**



TECHNOLOGY



- cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible
- Beam distance rated at 140/120 meters
- Spotlight, dual brightness white/color floodlight modes
- Powered by 3 AA Premium batteries (included)



XPP 5400 series

XPP 5400 series

NIGHTSTICK
Life Depends on Light™



Intrinsically Safe Permissible Multi-Function Headlamps

FEATURES: ALL MODELS

- Spotlight CREE® LED technology 50,000 hour life
- Spotlight – high/low-brightness white floodlight – green floodlight (5458)
- Focused spotlight beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Colored floodlight for night vision preservation (green-5458)
- Dual-Light™ (spotlight & any white floodlight mode at same time) for maximum versatility
- Engineered polymer housing
- Dual switches located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- Heavy-duty rubber strap for hard hat applications
- Waterproof
- Impact & chemical resistant
- Powered by 3 premium AA alkaline batteries (included)
- Limited Lifetime Warranty*



Rubber hardhat strap included

XPP-5458G White & Green Floodlight

Spotlight Switch

Spotlight

Two Level White Floodlight

High-Contrast Green



SAFETY RATING

cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible

Patent 7,738,229

Permissible Nightstick XPP-5458G Headlamp

MSHA APPROVAL No. 20-A130002-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: 1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EN91, and Energizer Type L91 batteries only.
2) Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only.
3) Replace the batteries in fresh air only.
4) Replace all batteries at the same time.
5) Do not mix batteries from different manufacturers or of different types.
6) The Model XPP-5458G Safety Headlamp must not be opened in areas where permeability is required.
7) The Model XPP-5458G Safety Headlamp is approved as a mine light under 30CFR, Part 20. It is not approve as a cap lamp under 30CFR, Part 19.

ETL CLASS I DIV 1 GRPS A-D T3 Ex ia I Ma CLASS I & II DIV 1 GRPS E-G T155C Ex ia IIC T3 Ga CLASS I ZONE 0 AEx ia IIC T3 Ga Intertek ITS 13 ATEX27838X ID 4003544 IECEx ETL 13 0025X INTRINSICALLY SAFE -20°C to Tamb to +40°C SECURITE INTRINSIQUE 1.5V/Cell AA Alkaline CE 0359

Conforms to:
ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11, ANSI/ISA 60079-26

Certified to:
CAN/CSA STD C22.2 No 157, CAN/CSA STD C22.2 No 60079-0, CAN/CSA STD C22.2 No 60079-11, CSA STD C22.2 No 25

INCLUDED

- Headlamp
- 3 premium alkaline AA batteries
- Elastic non-slip headband
- Rubber hardhat strap

XPP-5458G SPECIFICATIONS

- Lumens: spotlight-130, high white floodlight-100, low white floodlight-25, green floodlight-21, dual-light-190
- Run-time: spotlight-14 hrs, high white floodlight-12.5 hrs, low white floodlight-70 hrs, green floodlight-37 hrs, dual-light-6 hrs
- Beam distance: 120 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Width: 3.3in, height: 3.3in, depth: 3.5in, weight: 9.5oz

FL 1 STANDARD	DUAL-LIGHT	SPOTLIGHT
	190 LUMENS	130 LUMENS
	6h	14h
	132m	120m
	3500cd	3500cd
	2m	1m



1.800.KC.SUPPLY

www.kcsupply.com

1.800.527.8775

kcsupply@kcsupply.com

Feb 02, 2016