

Non-Pressure Rated

New - Protective Screen



Wing-Nut Style

Provides a secure closure by tightening the wing nut assembly
Available as six (6") LH or eight (8") LW inch diameter series

Cross-Arm Style

Self-locking strong-arm assembly flips down to close
Available in 6, 8, 10, 12, 16 and 20 inch diameter series
Series = LH, LA, LB, LS, LD, LE or LX Series



Cam-Lever Style

Cover is held down by multiple, adjustable cam levers
Available as twenty (20") KP or thirty (30") LT inch diameter series

Cross-Arm with Cam-Lever Style

Self-locking strong-arm assembly flips down to close while using the cam-levers for addition security
Available in twenty (20") KM or twenty-four (24") KN inch diameter series



Clamp-ring Style

A worm-gear clamp-ring attaches the cover to the weld ring
Inexpensive design for rarely opened covers
Available in sixteen (16") KF or twenty (20") KG inch diameter series

Clamp-ring with Cross-Arm Style

Dual opening cover allows filling while leaving manway closed
Only available with 10" fill cover
Main cover available with sixteen (16") KA or twenty (20") inch diameter series




Aluminum Hinged Clean Outs

Lightweight aluminum clean outs either flat or contoured to pipe diameter

Mechanical Latch Style

One-hand operation uses a quarter-turn latch to seal
Low profile available with curved radius too



Applications

Includes bin entry, clean-out, fill cover, hand holes, inspection door, manway, sampling port, and more
No tools required to open yet most can be locked to restrict access

Material

Available in Carbon Steel, Galvanized, Aluminum and Stainless Steel (304,316 and 316L)

Gasket

Options includes: Black Buna N, White Neoprene, EPDM, Hi-temp, Teflon, Viton and more