



# Great Stepped Silver Wall for Grain Entrapment Rescue V4.0

KC Supply has combined the strengths of two of the best designs to offer the ultimate adaptable entrapment rescue device

- No extra tools required
- External steps provide leverage for inserting panels
- Internal steps allow first responders to access trapped victim and supply 1st aid
- Durable #6005-T5 aluminum is less likely to bend from usage or pressure
- Fully extruded one-piece panel improves strength
- Smooth mill finish easily slides thru most grains
- Engineer tested with data
- Ball-and-socket pivot allows unlimited shapes, sizes and angles for one or numerous panels to create:
  - \* Round tube
  - \* Straight barrier wall
  - \* Horseshoe or C-shape
  - \* Works with all versions of the great wall

## Wall Dimensions Per Panel

- Width = 16"
- Height = 60"
- Weight = 25 lbs
- Assembled 6-panel ID = Approx 30 inches
- Assembled 8-panel ID = Approx 42 inches
- Storage = 12" depth for six stacked panels



Ball-and-socket joint allows each panel to pivot



## Platforms (4lbs)

- 18x18 poly
- Improves footing
- Durable with deep ribs



## Rescue Auger

Patent #9,139,372  
(25 lbs)

- Direct Drive
- Std 1/2" Drill



## Bolt-on Internal and External Steps

- Reduces valuable time for inserting panels
- Can't be misplaced
- Assists First Responders
- Aids in removal of victim

## Carrying Bag (10lbs):

- Durable, waterproof
- Handles on each end and each side
- Improves carrying / lifting / storage



1.800.527.8775

1.800.KC.SUPPLY

Rescue and Bin Entry  
Kits Available

Form #07142017

www.kcsupply.com

kcsupply@kcsupply.com



# Grain Entrapment Patented Red Rescue Auger

KC Supply's patented Red Rescue Auger quickly aids in the removal of grain which has entrapped a victim. The auger is powered by a standard drill with 1/2" chuck. Simply insert the auger's inlet into the grain and direct the discharge away from the victim.



- Powder-coated Steel
- Hand Grip
- Direct drive from power drill with 1/2" chuck
- Unloads 2.0 bushels per minute
- Guarded discharge
- Patented # 9,139,372

### General Specs

- 5-ft overall height
- 5.0" OD Inlet Guard
- 13" Discharge Width O.A
- 25 lbs



1/2 Inch Direct Drive Shaft

### Waterproof Bag:

Handles on sides and ends for ease of carrying / lifting



### Platforms (18x18)

Durable with deep, gripping ribs  
Provides more stable footing  
Use with any style of rescue tube

### Rope Kits Available



**1.800.527.8775**  
**1.800.KC.SUPPLY**

**www.kcsupply.com**  
**kcsupply@kcsupply.com**